

STEELVAPOR



Hose for hot water and saturated steam up to **17 BAR**;
Good resistance to chemicals and commercial cleansers.

TECHNICAL
CHARACTERISTICS

TUBE	High strength spiral wires.
REINFORCEMENT	High tensile synthetic plies and steel helix wire;
COVER	Red, smooth rubber, abrasion, ozone and weather resistant; Pin pricked to evacuate gases; Fabric impression.
TEMPERATURE	-40° C to +208° C
NORMS	BS 5342 - Type 2A

CODE	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight
	mm	inch	mm	inch	bar	psi	bar	psi	Kg/m
92S18R1325	13	1/2"	25	1"	17	250	170	2500	0,530
92S18R1628	16	5/8"	28	1 7/64"	17	250	170	2500	0,600
92S18R1932	19	3/4"	32	1 1/4"	17	250	170	2500	0,750
92S18R2538	25	1"	38	1 1/2"	17	250	170	2500	0,950
92S18R3246	32	1 1/4"	46	1 13/16"	17	250	170	2500	1,300
92S18R3854	38	1 1/2"	54	2 1/8"	17	250	170	2500	1,650
92S18R5168	51	2"	68	2 11/16"	17	250	170	2500	2,300